



Data Sheet Portable flexible tank PVC



Example

Manufactured from PVC-coated fabric, minimum tensile strength of 4000 N/5 cm, weight 1100 g/m². Equipped with:

- air vent/overflow, either in the form of a flexible tube or as a screw cap
- 4 pcs. D-Rings at narrow sides
- Hose coupling (Storz) complete with protective hood. Type, quantity and positioning of couplings to customer specification.
- Protective wrap-around holdall
- Repair set



Holdall with two carrying loops



Optional extra: protective ground sheet

Article number	Capacity [l]	Dimensions when filled (LxBxH) [m]	Packed dimensions (LxØ) [cm]	Nett weight w/out coupling [kg]
130001	1.000	1,7 x 1,5 x 0,5	50 x 30	13
130002	2.000	2,4 x 1,8 x 0,5	50 x 35	18
130003	3.000	2,8 x 2,2 x 0,6	60 x 45	22
130004	5.000	3,5 x 2,1 x 0,7	80 x 45	29
130006	10.000	5,5 x 2,7 x 0,8	80 x 60	47
130007	15.000	4,1 x 3,7 x 1,2	100 x 60	53
130008	20.000	5,1 x 3,6 x 1,2	120 x 65	63
130012	50.000	8,5 x 4,8 x 1,2	120 x 75	136
130021	150.000	14,0 x 8,0 x 1,4	140 x 120	322

Other sizes and customized versions available on enquiry.